

# SEAL UP®

## Original (Black) / White / Clear



### DESCRIPTION

Waterproofing repair sealant.

### TECHNICAL SHEET

### PROPERTIES

- Innovative 3 in 1 product: repairing, sealing, waterproofing.
- SEAL UP® Original (Black) distributes liquid bitumen which spreads into cracks.
- Used for sealing water leaks on roofs, rain pipes, roofing tiles and patios.
- Adapts to any substrate (wood, metal, plastic, cement, etc.) and any type of forms, conditions and application.
- Prevents the penetration of humidity into the treated surface.
- Resists even extreme conditions: rain, wind, sea water, etc.
- Excellent resistance to corrosion (“salt spray test” > 800 hours).
- Covers up to 21sqft / 2m2 depending on layer thickness.
- Surface dry within 2 hours and completely dry after 12-24 hours depending on layer thickness.
- Remains flexible and can be painted without any problems.
- Suitable for gaskets, PVC or metal tubes, ventilation outlets, car bodies, scaffolding, cracks in walls, etc.
- Long-lasting protection, anticorrosive and anti-scratch properties.

### AREAS OF APPLICATION

- Primarily for external protection.
- Bridges, roofs, pillars, steel structures, tanks, frames of agricultural machines, bodywork, etc.
- Waterproofing and protection of concrete or cement surfaces.
- Protection of materials in ports or in the railway industry.
- Electrical components (SEAL UP® Clear).
- Etc.

### APPLICATION

- Surface must be clean and dry product application.
- Shake can well for 60 seconds.
- Spray onto surface to be treated and on adjacent areas.
- Apply multiple layers.
- Apply during the cooler hours of the day.
- Store the product cool and not in direct sunlight.
- After usage turn can upside down and spray until nozzle is empty.



### TECHNICAL SPECIFICATIONS

Color	Black / White / Clear
Flash point (ASTM D56)	95°F / 35°C
Dry extract	63-67%
Curing time	2 hours /12 hours
Density	0.944
Crack Bridging Properties (SN EN 1062-7)	Class A2

### PACKAGING

CODE	SIZE
905 - Original (Black)	Can net Vol 10,14 fl oz Aerosol 650 ml
906 - White	
907 - Clear	