

ZINCCold Galvanizer

DESCRIPTION

Bright cold galvanizing for metal surfaces based on micronized 99.995% pure zinc powder.

TECHNICAL SHFFT

PROPERTY

- Pure zinc powder dispersed in a given resin.
- It is designed specifically for touch-up and repair of galvanized areas.
- Identical brilliant color obtained by galvanizing.
- Special anti-corrosion technology with mirror finish.
- Water, salt, grease and oil resistant.
- · High protection against oxidation
- · Abrasion resistant.
- Excellent adhesion.
- · Corrosion protection for welded joints.
- Quick drying.
- Does not run when used correctly.
- After drying, surface can be spray and brush painted.

APPLICATION SECTORS

- Mechanical workshops
- Carpenter
- Construction
- Hardware

HOW TO USE

- Make sure the treatment area is clean and rust free.
- Shake the can until you can hear the ball clicking against the walls of the can.
- Shake vigorously for about 90 seconds.
- Spray gun perpendicular to the surface being coated and keep a distance of about 30 cm (11.8 in).
- Once dry, apply a second coat if necessary.
- After usage turn can upside down and spray until nozzle is empty.

TECHNICAL FEATURES

Appearance	Bright light gray liquid
Flash point (ASTM D56)	Less than 0 °C
Smell	Typically
Relative density	1.0 gr/ml
Solubility in water	Insoluble
Lipid solubility	Soluble
Heavy metals	Not contain

PACKAGING

ITEM NUMBER	SIZE
105	Aerosol 400 ml

HEADQUARTERS EUROPE Resolv Sagl 6900 Lugano-Switzerland

info@resolv.swiss

AMERICA

Resolv America Corp. Miami, FL 33181 - USA info@resolvamerica.com

LATAN

Resolv Latam Panamá Ciudad - Panamá info@resolvlatam.com