

SEAL UP®

Hydrostop Fiber Grey

DESCRIPTION

Fiber-reinforced elastic waterproofing coating for remedying leakage, filling in cracks and a protective product for use in all weather conditions.

TECHNICAL SHEET

FEATURES

- Quick use in all weather conditions even on rain or snow.
- It repairs quickly, usable in all weather conditions even on rain or snow.
- Suitable on dry and wet surfaces.
- It adheres to all surfaces: aluminium, zinc, lead, glass, stone, asphalt, bitumen, solid PVC, roof tiles, wood, etc.
- It can be applied to vertical surfaces.
- It fills cracks and holes of several millimeters.
- Superelastic.
- Paintable with acrylic paints.
- Fully weather resistant.
- Primer not required.
- Not resistant to solvent.
- Not suitable for EPS panels and PVC sheets.

APPLICATION AREAS

- To repair leaks and cracks filling.
- To seal edges around chimneys, metal Trim, gutters, concrete cracks ,etc.
- To be used as a protective product.
- To seal inside and outside of buildings: balconies, terraces, roofs, fences, etc.
- Also suitable for road pipelines.
- For motorized vehicles and boats.

APPLICATION

- Clean the surface and remove inconsistent parts.
- Apply a thin layer of sealant to the cracks with a brush.
- If necessary over-apply a second layer after two days.
- If pasty , to spread it more easily, dilute it to 10% with nitro solvent or a hydrocarbon-based detergent.

CONSERVATION

Store in the original packing in a cool place and protected from direct sunlight, at a temperature between 5°C and 25°C for up to 24 months.

After this period, it does not necessarily mean that the sealant is unusable. The properties should be checked before application to ensure suitability for the intended use.

TECHNICAL PROPERTIES

Uncured sealant

Base	Synthetic resin with fiber-reinforced solvents
Appearance	Grey paste
Curing mechanism	Solvent evaporation
Curing time	24-48 h
Specific weight	1050 ± 10 kg/m ³
Application temperature	from -10°C to 40°C

Cured sealant

Elongation at break (%)	20 - 30
Temperature resistance	from -25°C to +100°C
Consumption	1 L / m ²

PACKAGING

Code	930
Format	1 L dose
Box	6 pieces
Pallet	110 boxes