

DESCRIPTION

Highly effective paint remover for all types of paint and glue, free from methylene chloride.

TECHNICAL SHEET

PROPERTIES

- Quickly removes old layers of paint and glue.
- Developed to remove all types of oil- and alkyd-based paints, emulsion paints, varnishes, and most two-component coatings.
- Can be used on metal, mineral, and wooden surfaces.
- Does not damage metal, mineral, or wooden substrates.
- Contains no methylene chloride.

APPLICATION AREAS

- Industry and industrial maintenance
- Construction and renovation
- Automotive sector
- Marine sector
- DIY and home improvement

APPLICATION

- Mechanically remove as much loose coating as possible (e.g. by scraping).
- Air, substrate, and material temperature must be between 0 and 30 °C, relative humidity below 85%.
- Use a disposable brush, flat or round. Do not use synthetic brushes.
- Apply a thick, even coat of REVO.
- Leave for approx. 10 to 60 minutes, or until the paint blisters and curls. Times are indicative and depend on the nature and thickness of the coating.
- Remove the lifted paint with a high-pressure water jet or a scraper.
- If several layers of old paint must be removed, the operation may need to be repeated.

Keep in cool, well-ventilated areas, protected from direct sunlight.

TECNICAL SPECIFICATIONS

Appearance	Pasty
Color	Pale yellowish
Odor	Characteristic
Density at 20° C	1.02 +/- 0.02 kg/l
Flammability	Flammable

PACKAGING

Code	150
Format	1 kg can
Box	6 pieces
Pallet	180 boxes
Shelf life	18 months