

ZINC

Cold Galvanizer

DESCRIPTION

Cold zinc coating with high corrosion protection, featuring excellent oxidation resistance, good abrasion resistance, and strong adhesion. Formulated with anticorrosion technology and mirror finish, composed of 99.995% pure zinc.

PROPERTIES

- Pure zinc powder dispersed in a given resin.
- It is designed specifically for touch-up and repair of galvanized areas.
- Identical brilliant color obtained by galvanizing.
- Special anti-corrosion technology with mirror finish.
- Water, salt, grease and oil resistant.
- High protection against oxidation
- Abrasion resistant.
- Excellent adhesion.
- Corrosion protection for welded joints.
- Quick drying.
- Does not run when used correctly.
- After drying, surface can be sprayed and brush painted.

APPLICATION AREAS

- Mechanical workshops
- Carpenter
- Construction
- Hardware

APPLICATION

- Make sure the treatment area is clean and rust free.
- Shake the can until you can hear the ball clicking against the walls of the can.
- Shake vigorously for about 90 seconds.
- Spray gun perpendicular to the surface being coated and keep a distance of about 30 cm (11.8 in).
- Once dry, apply a second coat if necessary.
- After usage turn can upside down and spray until nozzle is empty.

TECHNICAL SPECIFICATIONS

Appearance	Bright light gray liquid
Flash point (ASTM D56)	Less than 0 °C
Smell	Typically
Relative density	1.0 gr/ml
Solubility in water	Insoluble
Lipid solubility	Soluble
Heavy metals	Not contain

PACKAGING

Code	920
Format	Aerosol 520 ml (netto 400 ml)
Box	12 pieces
Pallet	60 boxes